



dayGraphica 8395

Breeze through demanding press runs

dayGraphica 8395's specially designed durable carcass and superior print surface meets the rigorous demands of a newspaper pressroom. The 8395 runs great on double - and single width presses, this versatile packed blanket can also be used on certain presses in a no-pack mode. Longer life, less down time and better printing quality on press, gives you higher productivity, lower operating costs, maximum profitability and no missed deadlines.

The patented closed cell compressible layer gives the dayGraphica 8395 precise and even printing pressure - across the entire printing surface. This new carcass is engineered for unsurpassed resistance to gauge loss, smashes and to wraps, to keep you running without blanket changes. And it offers great rebound, too. The ground surface carries the optimum amount of ink for newspaper printing and you can expect the 8395 to meet your quality standards for contrast values, dot gain and density.

Features

Benefits

Highly ground surface.	Uniform gauge and consistency. Ideal texture for carrying and transferring ink. Maximum release characteristics. Precise printability and easier washing. Fewer stops for retensioning and longer blanket life.
Compatible rubber surface compound.	Solvent resistant. Excellent abrasion resistance. Excellent release characteristics. More consistent feed characteristics.
Durability engineered carcass.	High density carcass minimises gauge loss and provides longer life on press and more consistent print quality.
Patented closed-cell compressible layer.	Enables blanket to achieve precise and even printing pressure across entire printing surface. Maximum smash resistance. Key factor in blanket durability. Rebounds quickly.
Application versatility.	Designed to allow flexibility in packing requirements.

Specifications

Colour:	Brown
Surface:	Ground
Thickness:	1.95mm
Hardness:	78° Shore A
Compressibility:	0.13mm @ 1060 kpa Typical 0.18mm @ 2060 kpa Typical
Elongation:	<0.70% @ 10 N/mm
Tensile Strength:	>60 N/mm
Face Compound:	Solvent resistant rubber blend

Optimise your on-press performance

Over the years, Day's printing technologists and pressroom chemists have learned the dynamics between printing blankets and pressroom chemicals play a vital role in on-press performance and profitability. And they've learned how to analyse these dynamics to help printers resolve problems and optimise their printing results.

Day's laboratory experts, technical support team and sales consultants work together with printers to recommend the right combination of pressroom chemicals and printing blankets to achieve optimum performance. A consultative service offered only by Day International.



Day International
Balgray Street,
Dundee, DD3 8HN,
Scotland.

T +44 (0)1382 422200
F +44 (0)1382 819051
E day.uk@flintgrp.com
www.dayintl.com

FlintGroup