

dayGraphica 8897 Newsprinter Packed

Breeze Through Demanding Press Runs

The 8897's specially designed durable carcass and superior print surface makes the rigorous demands of a newspaper pressroom like a walk in the park. This mean longer blanket life, less down time and better printing quality on press. All of those pluses equate to higher productivity, lower operating costs, maximum profitability and no missed deadlines. Use the 8897 for great press runs on double or single width presses.

Features

Benefits

Highly ground surface	<ul style="list-style-type: none"> Uniform gauge and consistency. Ideal texture for carrying and transferring ink. Maximum release characteristics. Precise printability.
Compatible rubber surface compound	<ul style="list-style-type: none"> Solvent resistant. Excellent abrasion resistance. Excellent release characteristics. More consistent feed characteristics.
Durability engineered carcass	<ul style="list-style-type: none"> High density carcass prevents gauge loss and provides long life.
Patented closed-cell compressible layer	<ul style="list-style-type: none"> Enables blanket to achieve precise and even printing pressure across entire printing surface. Maximum smash resistance. Key factor in blanket durability. Rebounds quickly.
Application versatility	<ul style="list-style-type: none"> Designed to allow flexibility in packing requirements

Specifications

Color:

Brown

Surface:

Ground

Thickness:

4 Ply 1,95mm/.077" Nominal

Face Compound:

Solvent Resistant Rubber Blend


Hardness:

78° Shore A Typical

Compressibility Deflection:

4 Ply 0,13mm at 1060 kpa/
.005" at 154 psi Typical

4 Ply 0,18mm at 2060 kpa/
.007" at 299 psi Typical



For more information about this Day product, contact us at 800-525-6510 visit us online at www.dayintl.com



Day International Inc.
130 West Second Street
Suite 1700
Dayton, OH 45402
T +1 800 877 8187
www.dayintl.com